



GLOSS

Floor Finish

Hilway Direct Gloss Floor Finish is a high solids (28% solids) field-applied acrylic finish with a lustrous shine that is a durable, highly scuff-resistant, protective coating for use on most resilient and hard surface floors.



High-Gloss Shine & Superior Durability

- High Solids Content (28%) for dependable Durability
- Excellent Wear & Scuff Resistance
- High-Gloss, Wet-look Shine
- No VOCs
- No Yellowing

Flooring Types

- Sheet Vinyl
- Rubber
- LVT
- Marble
- VCT
- Linoleum
- Concrete
- Terrazzo
- Cork
- Slate
- Quarry Tile
- Asphalt Tile

Environments

- Healthcare
- Schools & Universities
- Institutional
- Office Buildings

Additional Product Information

- ▢ Gloss Level: 60 (based on Gloss Scale)
- ▢ Scuff & stain resistant finish.
- ▢ Safe for use on sensitive flooring types.
- ▢ Only 2-3 coats required for initial application.
- ▢ Cleans routinely with Hilway Direct Neutral Cleaner.
- ▢ Non-hazardous, no VOCs.
- ▢ Exceptionally durable Acrylic finish.

Directions for Use

Initial Application Coverage:

Single coat (undiluted): 1500-2000 square feet per 1.33 gallon depending on porosity of flooring material. 2-3 coats required for Initial Application. (See product label for detailed instructions.)

Application Directions:

Remove loose dirt and soil. Thoroughly clean floor or remove coating as applicable. Rinse and neutralize floor with clean water. Apply Hilway Direct Gloss undiluted in a thin, even coat using a microfiber applicator mop. Apply 2-3 coats. Allow each coat to air dry completely (generally 30-60 minutes) before applying next coat. Allow floor surface to dry overnight before heavy traffic use. (See product label for detailed instructions.)

Details

- ▢ 1.33 Gallon Container
- ▢ 28% Solids
- ▢ VOC Free
- ▢ Mild, pleasant fragrance
- ▢ Non-flammable liquid
- ▢ Protect from freezing
- ▢ Avoid contact with sensitive surfaces such as wood, metal, furnishings
- ▢ Commercial & Industrial Use ONLY
- ▢ Read complete product label & MSDS sheet prior to use.