



# PLUS

## Floor Finish & Cleaner/Maintainer

### INSTRUCTIONS FOR USE & COVERAGE

#### Initial Application Directions:

**1.** Dry sweep then damp mop floor to remove loose dirt and soil from floor. Thoroughly clean floor with Hilway Direct Neutral Cleaner or Allsafe Stripper or flooring manufacturer's recommended product. **2.** If flooring has a factory or site-applied acrylic coating, remove coating following flooring manufacturer's instructions. This usually can be done with Hilway Direct Allsafe Stripper diluted 1:5 or 1:10 with clean water, or flooring manufacturer's recommended product diluted as directed, in an auto scrubber or low rpm swing machine with a red pad or equivalent. Always rinse and neutralize floor with clean water after removing old coating. Do not let stripper solution dry on floor. **3.** Shake **Hilway Direct Plus** vigorously for 30 seconds then let it settle for 5 minutes. Apply undiluted in a thin, even coat using a microfiber applicator mop. Do not use treated dust mops. **4.** Apply 2-3 coats. Allow each coat to air dry completely (generally 30-60 minutes) before applying next coat. **5.** Allow floor surface to dry overnight before heavy traffic use.

#### Initial Application Coverage:

Undiluted, single coat: 1500 – 2000 square feet/ 1.33 gallons. Coverage may vary depending on porosity of flooring material.

#### Daily Cleaning, Mop & Bucket Directions:

**1.** Sweep floor to remove loose dirt & soil. **2.** Add 1 ounce of **Hilway Direct Plus** to 1 gallon warm water. Mop floor with the solution. **3.** A 2-bucket system is highly recommended. Bucket 1 for Hilway Direct Plus solution and bucket 2 for clean water to rinse mop. **4.** Pick up soil and excess solution with a clean, tightly wrung out mop. **5.** Do not rinse floor after cleaning. **6.** Allow floor air dry completely.

#### Daily Cleaning, Auto Scrubbing Machine Directions:

**1.** Add 1 ounce of **Hilway Direct Plus** to 1 gallon warm water. **2.** Scrub floor with solution. **3.** Trail mop excessive wet areas behind scrubber. **4.** Do not rinse floor after cleaning. **5.** Allow floor to air dry completely.

**For Use On:** Sheet Vinyl, LVT, VCT, Rubber, Linoleum, Cork, Asphalt Tile, Marble, Slate, Concrete, Quarry Tile, or Terrazzo Flooring.

**Caution:** Eye irritant. Avoid contact with skin and eyes. Do not taste or swallow. In case of contact with eyes or skin flush with plenty of water. If irritation develops, seek medical attention. In case of ingestion, flush mouth with water, drink large quantities of water and seek immediate medical attention, **DO NOT** induce vomiting. **KEEP OUT OF REACH OF CHILDREN.**

**Note:** Avoid solution contact with sensitive surfaces such as wood, metal, furnishings. When applying finish, avoid strong sunlight and drafts. Turn off under floor heat prior to application. Read full MSDS and product label prior to use. For Commercial & Industrial Use ONLY.

**Handling and Storage:** Protect from freezing. Recommended storage temperature: 68°F (20°C). Avoid storing in direct sunlight and high temperatures. Do not store near food.